

# **Material Safety Data Sheet**

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 3M<sup>TM</sup> ESPE<sup>TM</sup> EXPRESS<sup>TM</sup> 2 LIGHT BODY FLOW QUICK REFILL

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

# EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 10/31/14 **Supercedes Date:** 10/10/06 **Document Group:** 21-9854-7

### **ID** Number(s):

70-2011-2407-3

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

21-2017-8, 21-9345-6

# **Revision Changes:**

Kit: Component heading paragraph information was modified.

Page Heading: Product name information was modified.

Kit: Product name information was modified.

Kit initial issue message information was modified.

Section 1: Manufacturer name information was added.

Section 16: Disclaimer (first paragraph) information was added.

Section 16: Disclaimer (second paragraph) information was added.

Kit: ID Number Heading information was added.

Kit: ID Number(s) information was added.

Section 16: Web address information was added.

Section 1: Address information was added.

Copyright information was added.

Company logo information was added.

Telephone header information was added.

# MATERIAL SAFETY DATA SHEET 3MTM ESPETM EXPRESSTM 2 LIGHT BODY FLOW QUICK REFILL 10/31/14

Company Telephone information was added.

Section 1: Emergency phone information information was added.

Company Logo information was deleted.

Copyright information was deleted.

Kit: Manufacturer's name information was deleted.

Kit: Emergency phone information information was deleted.

Kit: Disclaimer (first paragraph) information was deleted.

Kit: Disclaimer (second paragraph) information was deleted.

Kit: Address line 1 information was deleted.

Kit: Address line 2 information was deleted.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



# **Safety Data Sheet**

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

21-2017-8 9.00 **Document Group: Version Number:** 10/09/14 01/19/08 **Issue Date: Supercedes Date:** 

# **SECTION 1: Identification**

### 1.1. Product identifier

3MTM ESPETM EXPRESSTM 2 LIGHT BODY FLOW QUICK BASE

### **Product Identification Numbers**

LE-F100-0228-9

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Impression material

#### Restrictions on use

For use only by dental professionals.

# 1.3. Supplier's details

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA 1-888-3M HELPS (1-888-364-3577) **Telephone:** 

# 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. Label elements

# Signal word

Not applicable.

### **Symbols**

Not applicable.

#### **Pictograms**

Not applicable.

#### 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
VINYL POLYDIMETHYLSILOXANE	68083-19-2	40 - 50 Trade Secret *
CRISTOBALITE	14464-46-1	30 - 40 Trade Secret *
DIMETHYL METHYL HYDROGEN SILICONE	68037-59-2	10 - 15 Trade Secret *
FLUID		
SILANE TREATED SILICA	67762-90-7	1 - 10 Trade Secret *
POLYETHYLENE GLYCOL, SILOXANE	27306-78-1	1 - 5 Trade Secret *
TERMINATED		

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

# **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eve Contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

Substance Carbon monoxide **Condition** 

**During Combustion** 

Page 2 of 9

Carbon dioxide Irritant Vapors or Gases **During Combustion During Combustion** 

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component

for the component.				
Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
CRISTOBALITE	14464-46-1	ACGIH	TWA(respirable	A2: Suspected human
			fraction):0.025 mg/m3	carcin.
CRISTOBALITE	14464-46-1	OSHA	TWA concentration(as total	
			dust):0.15 mg/m3;TWA	
			concentration(respirable):0.05	
			mg/m3(1.2 millions of	
			particles/cu. ft.)	
SILANE TREATED SILICA	67762-90-7	CMRG	CEIL:5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

See Section 7.1 for additional information on skin protection.

### Respiratory protection

Respiratory protection is not required.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Solid **General Physical Form: Specific Physical Form:** Paste

Odor, Color, Grade: Odorless, white paste **Odor threshold** No Data Available рH Not Applicable **Melting point** No Data Available **Boiling Point** Not Applicable

**Flash Point** Flash point > 93 °C (200 °F)

**Evaporation rate** Not Applicable Not Classified Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Not Applicable **Vapor Pressure** Not Applicable **Vapor Density Density** 1.2 - 1.3 g/cm<sup>3</sup>

**Specific Gravity** 1.2 - 1.3 [*Ref Std:* WATER=1]

Solubility in Water Negligible Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available No Data Available Viscosity **Volatile Organic Compounds** Not Applicable

Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

# 10.5. Incompatible materials

Amines Strong bases Strong oxidizing agents Strong acids

# 10.6. Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

# 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### **Inhalation:**

No health effects are expected.

# **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

#### **Eye Contact**:

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u> <u>C.A.S. No.</u> <u>Class Description</u> <u>Regulation</u>
--

Page 5 of 9

SILICA, CRYS AIRRESP	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Acute Toxicity			
Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
VINYL POLYDIMETHYLSILOXANE	Dermal	Rabbit	LD50 > 15,440 mg/kg
VINYL POLYDIMETHYLSILOXANE	Ingestion	Rat	LD50 > 15,440 mg/kg
CRISTOBALITE	Dermal		LD50 estimated to be > 5,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Inhalation-	Rat	LC50 4.2 mg/l
	Dust/Mist		
	(4 hours)		
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Ingestion	Rat	LD50 > 2,000  mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000  mg/kg
SILANE TREATED SILICA	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Dermal	Rabbit	LD50 > 2,000 mg/kg
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Inhalation-	Rat	LC50 2 mg/l
	Dust/Mist		
	(4 hours)		
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name	Species	Value
VINYL POLYDIMETHYLSILOXANE	Rabbit	No significant irritation
CRISTOBALITE		No significant irritation
SILANE TREATED SILICA	Rabbit	No significant irritation
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
VINYL POLYDIMETHYLSILOXANE	Rabbit	Mild irritant
SILANE TREATED SILICA	Rabbit	No significant irritation
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Rabbit	Severe irritant

# **Skin Sensitization**

Name	Species	Value
SILANE TREATED SILICA	Human	Not sensitizing
	and	
	animal	
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Guinea	Not sensitizing
	pig	

**Respiratory Sensitization** 

_	AT	G	
1 1	Name	Species   Value	

**Germ Cell Mutagenicity** 

Name	Route	Value
CRISTOBALITE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
CRISTOBALITE	In vivo	Some positive data exist, but the data are not
		sufficient for classification
SILANE TREATED SILICA	In Vitro	Not mutagenic
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	In Vitro	Not mutagenic

POLYETHYLENE GLYCOL, SILOXANE TERMINATED	In vivo	Not mutagenic

# Carcinogenicity

Name	Route	Species	Value
CRISTOBALITE	Inhalation	Human	Carcinogenic
		and	_
		animal	
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
POLYETHYLENE GLYCOL, SILOXANE TERMINATED	Ingestion	Some positive reproductive/developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 450 mg/kg/day	premating & during gestation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name Route Target Organ(s) Value	Species Test Result Exposure Duration
----------------------------------	---------------------------------------

Specific Target Organ Toxicity - repeated exposure

specific ranger organ romenty repeated exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CRISTOBALITE	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
SILANE TREATED SILICA	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

# **Aspiration Hazard**

	T = = = = = =	
N	lame	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

# **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

# 15.2. State Regulations

Contact 3M for more information.

### **15.3.** Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### **NFPA Hazard Classification**

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 21-2017-8
 Version Number:
 9.00

 Issue Date:
 10/09/14
 Supercedes Date:
 01/19/08

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



# **Safety Data Sheet**

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

21-9345-6 5.00 **Document Group: Version Number:** 10/09/14 01/28/08 **Issue Date: Supercedes Date:** 

# **SECTION 1: Identification**

#### 1.1. Product identifier

3MTM ESPETM EXPRESSTM 2 LIGHT BODY FLOW QUICK CATALYST

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Impression Material

1.3. Supplier's details

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 2.2. Label elements

# Signal word

Not applicable.

### **Symbols**

Not applicable.

### **Pictograms**

Not applicable.

# 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
VINYL POLYDIMETHYSILOXANE	68083-19-2	40 - 50 Trade Secret *
CRISTOBALITE	14464-46-1	40 - 50 Trade Secret *
POLY(DIMETHYLSILOXANE)	63148-62-9	1 - 5 Trade Secret *
SILANE TREATED SILICA	67762-90-7	1 - 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring Combustion

# 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

# 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

# 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
CRISTOBALITE	14464-46-1	ACGIH	TWA(respirable	A2: Suspected human
			fraction):0.025 mg/m3	carcin.
CRISTOBALITE	14464-46-1	OSHA	TWA concentration(as total	
			dust):0.15 mg/m3;TWA	
			concentration(respirable):0.05	
			mg/m3(1.2 millions of	
			particles/cu. ft.)	
SILANE TREATED SILICA	67762-90-7	CMRG	CEIL:5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

# 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

Page 3 of 8

#### 3M<sup>TM</sup> ESPE<sup>TM</sup> EXPRESS<sup>TM</sup> 2 LIGHT BODY FLOW QUICK CATALYST 10/09/14

protection(s) are recommended: Safety Glasses with side shields

### Skin/hand protection

See Section 7.1 for additional information on skin protection.

# **Respiratory protection**

Respiratory protection is not required.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**General Physical Form:** Solid **Specific Physical Form:** Paste

Odor, Color, Grade: Odorless, blue paste **Odor threshold** No Data Available pН Not Applicable **Melting point** No Data Available **Boiling Point** Not Applicable

Flash point > 93 °C (200 °F) **Flash Point** 

**Evaporation rate** Not Applicable Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Vapor Pressure Not Applicable **Vapor Density** Not Applicable **Density** 1.3 - 1.4 g/cm3

1.3 - 1.4 [Ref Std: WATER=1] **Specific Gravity** 

Solubility in Water Negligible Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available **Volatile Organic Compounds** Not Applicable Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

# 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

# 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Amines Strong acids

Strong bases

Strong oxidizing agents

# 10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### **Inhalation:**

No health effects are expected.

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

# **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
SILICA, CRYS AIRRESP	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

Page 5 of 8

the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
VINYL POLYDIMETHYSILOXANE	Dermal	Rabbit	LD50 > 15,440 mg/kg
VINYL POLYDIMETHYSILOXANE	Ingestion	Rat	LD50 > 15,440 mg/kg
CRISTOBALITE	Dermal		LD50 estimated to be > 5,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
POLY(DIMETHYLSILOXANE)	Dermal	Rabbit	LD50 > 19,400 mg/kg
POLY(DIMETHYLSILOXANE)	Ingestion	Rat	LD50 > 17,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
VINYL POLYDIMETHYSILOXANE	Rabbit	No significant irritation
CRISTOBALITE		No significant irritation
SILANE TREATED SILICA	Rabbit	No significant irritation
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
VINYL POLYDIMETHYSILOXANE	Rabbit	Mild irritant
SILANE TREATED SILICA	Rabbit	No significant irritation
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation

# **Skin Sensitization**

Name	Species	Value
SILANE TREATED SILICA	Human	Not sensitizing
	and	
	animal	

**Respiratory Sensitization** 

Name	Species	Value

**Germ Cell Mutagenicity** 

our mountaines		
Name	Route	Value
CRISTOBALITE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
CRISTOBALITE	In vivo	Some positive data exist, but the data are not
		sufficient for classification
SILANE TREATED SILICA	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
CRISTOBALITE	Inhalation	Human	Carcinogenic
		and	
		animal	
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509	1 generation

				mg/kg/day	
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497	1 generation
		_		mg/kg/day	
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL	during
		_		1,350	organogenesi
				mg/kg/day	S

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

	0	0		0 1				
Name			Route	Target Organ(s)	Value	Species	Test Result	Exposure
								Duration

Specific Target Organ Toxicity - repeated exposure

Specific Target Organ Toxicity - repeated exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
CRISTOBALITE	Inhalation	silicosis	Causes damage to organs through prolonged or repeated	Human	NOAEL Not available	occupational exposure
			exposure			
SILANE TREATED	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational
SILICA		silicosis			available	exposure

**Aspiration Hazard** 

Name	Value
------	-------

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

# **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit <a href="http://3M.com/Transportinfo">http://3M.com/Transportinfo</a> or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

Page 7 of 8

# 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

#### **15.3.** Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

# NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 21-9345-6 **Version Number:** 5.00 **Issue Date:** 10/09/14 **Supercedes Date:** 01/28/08

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com